

Professional Window Cleaning Equipment



Mobile Starter Kit – MOBI™ Start

Suitable for purifying up to 400 litres of water at 100ppm ingoing TDS (total dissolved solids).

Kit consists of:-

- 1x male tap connector to fit standard ½” and ¾” tap threads
- 1x hose assembly (1-metre) with tape and stop connectors to connect the mains water to the filter
- 1x filter with garden hose type inlet/outlet connectors
- 1x hose assembly (10-metres) with tap and stop connectors to connect filter to the telescopic pole
- 1x telescopic pole with flow control valve, Lite-5® pole tubing and angled crank to connect to brush
- 1x window cleaning brush with a pair of fanjet nozzles and tubing to connect to the pole hose
- 1x TDS meter for testing water quality and checking state of the resin medium

The new MOBI™ Start Mobile DI Filter filled with demineralising resin, for pure water spot-free cleaning.

- Simple, quick, inline filtering method for a spot-free finish on windows, glass facades, fascias, conservatory roofs, etc.
- Practical male inlet/outlet hoselock type quick connectors for easy hose connection/disconnection.

OPERATING SPECIFICATIONS

- Dry Weight (with Resin): 3.0kg
- Wet Weight (with Resin): 5.0kg
- Max Width: 135mm
- Max Height: 385mm
- Max Depth: 100mm
- Min Temperature: 1°C (34°F)
- Max Temperature: 50°C (122°F)
- Max Pressure: 10.5bar (150psi)

DO NOT EXCEED SPECIFICATIONS

HANDLING INSTRUCTIONS

- Vessel approved for water filtration use for spot-free cleaning purposes only.
- Do not use for pneumatic or hydro-pneumatic applications.
- Dispose of filter in its entirety when resin medium has become spent, ie. once the resin medium produces readings beyond 10ppm. Remember to remove inlet/outlet connectors for re-use.

CAUTION - Frost will cause damage to the vessel and/or hoses and connectors – to prevent frost damage do not leave this equipment exposed to temperatures below 1°C.

